(City use only) CD-#:
City Staff Initials/Date:

CITY OF FOLSOM
Community Development Department

Stormwater Quality Control Measures Approval Form
(Must be completed by applicant prior to final project approval)

Project Name:_____

Project Address:_____ APN(s):_____

Applicant/Contact:_____Phone/Email:_____

Owner/Developer Information:

Name/Company:_____Mailing Address:_____

Phone/Fax:_____ City/State:_____ Zip Code:_____

Project Size: _____(acres) Area Disturbed:_____(acres)

Drainage Shed/Receiving Water:

- ☐ Alder Creek South
- ☐ Alder Creek West
- ☐ Am. River North
- ☐ Am. River South
- ☐ Hinkle Creek East
- ☐ Hinkle Creek West
- ☐ Humbug Crk North
- ☐ Humbug Crk North
- ☐ Linda Creek
- ☐ Willow Creek North
- ☐ Willow Creek South

Does site runoff drain to existing stormwater quality detention basin? ☐ No ☐ Yes _____
(state location)

DEVELOPMENT CATEGORY: *(Check all that apply)*

- ☐ Residential (Single Family)
- ☐ Residential (Multi-Family)
- ☐ Commercial (≧ 1 Acre)
- ☐ Restaurants (≧ 1 Acre)
- ☐ Hillside Developments (≧ 25% slope)
- ☐ Auto Repair Shops
- ☐ Streets/Roads/Highways (≧ 5 Acres)
- ☐ Retail Gasoline Outlets (≧ 1 Acre)
- ☐ Parking Lots (≧ 5000 sf or 25 spaces)

PERMANENT SOURCE CONTROL MEASURES INCORPORATED [1]: *(Check all that apply)*

- ☐ Material Storage
- ☐ Outdoor Loading/Unloading
- ☐ Vehicle Fueling
- ☐ Vehicle Maint/Repair/Washing
- ☐ Outdoor Process Equipment O&M
- ☐ Waste Handling
- ☐ Storm Drain Stencil/Marking

PERMANENT TREATMENT CONTROL MEASURES INCORPORATED [1]: *(Check all that apply)*
(Attach design methods, calculations, schematics and 81/2 x 11 site plan showing location of control measure(s))

- ☐ Water Quality Basin/Pond [2]
- ☐ Vegetative Swale
- ☐ Media Filtration
- ☐ Vegetative Filter Strip
- ☐ Infiltration Basin
- ☐ Porous Pavement
- ☐ Surface Infiltration Trench
- ☐ Proprietary Device [3] Type and Model No._____

Notes

(1) Approved control measures and design information can be obtained from the *Guidance Manual for On-Site Stormwater Control Measures* (Jan 2000) by the Sacramento Stormwater Quality Partnership – www.sacstormwater.org
(2) Water quality basins shall be designed in accordance with City and County of Sacramento design requirements (using Sato curves) or the California Stormwater Quality Association's handbook for new development and redevelopment (2003).
(3) For updates on currently accepted devices, see: http://www.msa.saccounty.net/sactostormwater/newdevelopment/treament-options.asp